A complete solution in a box

Monarch 9662 economical wide web printer







"Concept to Checkout" By Owen Smith

Monarch 9662 tabletop bar code printer packed full of features

Monarch 9662 printer.

The economical 9662 offers high performance thermal direct/transfer printing with the capability to print 6" (152mm) wide labels or tags. Its robust and rugged construction means it is able to withstand the harshest of environments and is the ideal solution for applications which require a 6" wide label.

Ideal for Compliance labelling including:


- ODETTE which is used in the Automotive industry.
- EAN 128 shipping labelling.
- AIAG which is used in the chemical industry.
- Healthcare labelling.

(35)PWG IDX

1234567890


This type of labelling ensures the smooth flow of goods between trading partners in these industries and helps improve efficiency and productivity within companies. In addition to compliance labelling the 9662 can also be used for Production Identification in a variety of heavy industries.







ODETTE label format



Ship From:

Paxar Paxar House, Central Road, Harlow, Essex

The 9662 - a complete solution in a box.

The 9662 offers users quick set up enabling label printing to start in a matter of minutes. The 9662 comes complete with the following:

- Windows drivers for Win 3.11, 9X, 2K, ME, XP and NT.
- Label design software that lets the user create and print labels, including bar codes, text and graphics.
- Sample label and ribbon roll.

Key features of the printer include:

- ✓ Thermal direct/transfer printer.
- ✓ Can print on demand or in continuous mode.
- ✓ Prints tags or labels.
- ✓ Metal cover as standard.
- ✓ 203dpi printhead.
- ✓ Fast 32 bit processor.
- ✓ Printhead width 6" (152mm).
- ✓ Memory 2MB DRAM.
- ✓ Print speed 6" (152mm) per second.
- ✓ 32 character 2 line display.
- ✓ Serial & Parallel communications.
- ✓ Maximum label size 6" x 30" (152mm x 760mm).
- ✓ All 1D and 2D barcode symbologies supported.



Pallet label format

Benefits of the 9662 printer:

- Durable media and print head completely protected from dust and dirt inside metal casing.
- Value for money packed full of features, including serial and parallel communications as standard.
- ✓ Easy to use a display that is easy to read and understand means minimum operator training.
- Extensive range of accessories available Argokee keypad, cutter, dispenser and font/flash expansion.



Standard Features

Printing Method

Thermal Transfer/Direct

Dimensions

Height 260mm (10.2") Width 310mm (12.1") Depth 445mm (17.3") Weight 14.5kg (32.6lbs)

Printhead

152mm wide (6") 203 DPI – 8 dots/mm

PC/Host Interface

Centronics Parallel RS-232 Serial

Memory

32-Bit Processor 2Mb DRAM, 1MB Flash ROM

Standard Fonts

International character sets 5 alphanumeric fonts 1.25mm – 6mm expandable x 24 Soft fonts downloadable with optional 512Kb card

Display

2 lines, 16 character LCD

Case

Rugged metal case with moulded plastic front

Bar Code Symbologies

- EAN 8, 13, +2, +5, 128
- UPC A, E, +2, +5
- Interleaved 2 of 5
- Extended Code 39
- Codabar
- Code 128 (Subset A, B, C)
- Code 93
- Code 128 UCC
- MAXICODE
- PDF417
- POSTNET
- Matrix 25

Optional Accessories

512Kb card for downloading soft fonts Standalone keyboard Real time clock

Supply Sizes

Widths 152mm (6.0") Lengths 25mm to 760mm (1" to 30") Supply roll contains 152 meters of supply Ribbon rolls contain 360 meters of ribbon

Ribbon Widths

6" (152cm)

Maximum Print Area

152mm x 760mm (6.0" x 30")

Performance

Power

220 V / 50Hz

Printing Rate

51mm - 152mm (2.0" - 6.0") per second

Environment

Temperature

Operating 40°F to 100°F (4C° to 38°C)

Humidity

Operating and storage 10% to 90% non condensing

GOMARO s.a. - CH 1123 Aclens - Switzerland Tel: 021 869 97 70 Fax: 021 869 96 02

www.gomaro.ch Contact info@gomaro.ch





©2002 Paxar UK Ltd All rights reserved - Printed in the UK