

## **IMAGETEAM™ 4800**

### *Industrial 2D Area Imager*



### **Features**

*Powered by Adaptus™ imaging technology - Delivers extraordinary reading performance to enable ease-of-use and reader versatility.*

*Aggressive, omni-directional point-and-shoot reading of linear, PDF417, and full 2D matrix symbols offers ease-of-use and greater throughput.*

*Rugged Packaging – Impact absorbent, shock resistant housing withstands fifty 6.5 foot (2 meter) drops, and is sealed to resist dust, water, and contaminants from entering the unit. Backed by an industry-best 3 year warranty.*

*Future-Proofed Technology - The versatility of Adaptus serves broad image-based data capture needs today, and protects your investment against future application demands.*

*Adaptus Editing Software – Eases the transition to full 2D matrix data acquisition transfer without expensive host software modifications.*

The IMAGETEAM™ 4800 Industrial 2D Area Imager is the first hand held area image reader powered by Adaptus™ imaging technology. Adaptus technology decodes faster, farther, and future-proofs your investment. This means your workers spend less time trying to capture data, and more time using this data to make your business more cost efficient.

Whether your application is reading conventional linear bar codes or tomorrow's 2D matrix symbolologies, the IT4800 can capture them all today. If your application requires signature capture, OCR, or digital photography, the IT4800 can solve them all. Its advanced imaging optics software quickly and easily determines the image content and transfers it to your host system. In fact, full image transfer can be accomplished in less than one second through its on-board full speed USB interface.

The IT4800 can be used in a wide range of applications from circuit board manufacture to package delivery tracking. In addition, bar codes, images, and signature capture can provide positive proof of delivery. If discrepant material needs to be viewed by a production supplier, images can be captured and quickly transferred for immediate review and resolution, saving time and money.

Because these applications often contain challenges for many image capture devices, we have made the IT4800 extra tough. Full shock-absorbing rubber protects the imager from dozens of 6.5 feet (2 meter) drops to concrete. Many application environments exhibit airborne dust and rain, so we have sealed the IT4800 so these elements will not degrade performance. In addition to an IP54 enclosure specification, the IT4800 is backed by an industry-best 3-year warranty.

For applications that demand superior aiming, the IT4800 is the best choice. Integrated red aiming optics ensures the best aimer visibility for exceptional point-and-shoot performance. This ensures your operator will find and capture the correct image every time.

**Upgrade your image.**



# IMAGETEAM™ 4800 Specifications

## Performance

<b>Aiming:</b>							
Illumination LEDs	626nm ±30nm						
Aiming LEDs	626nm ±30nm						
<b>Image:</b>	VGA, 640x480. Binary, TIFF, or JPEG output.						
<b>IT4800SR Working Range:</b>	<b>8 mil Linear (.020cm)</b>	<b>10 mil PDF417 (.025cm)</b>	<b>13 mil UPC (.033cm)</b>	<b>6.6 mil PDF417 (.017cm)</b>	<b>15 mil Data Matrix (.038cm)</b>	<b>35 mil MaxiCode (.089cm)</b>	
<b>Near</b>	2.9 in. (7.4cm)	2.5 in. (6.4cm)	1.9 in. (4.8cm)	3.9 in. (9.9cm)	3.1 in. (7.9cm)	1.4 in. (3.6cm)	
<b>Far</b>	7 in. (17.8cm)	8.4 in. (21.3cm)	11.9 in. (30.2cm)	5.7 in. (14.5cm)	5.9 in. (15cm)	12.4 in. (31.5cm)	
<b>Skew Angle:</b>	±40°						
<b>Pitch Angle:</b>	±40°						
<b>Horizontal Velocity:</b>	2 in. (5 cm) per second						

## Mechanical/Electrical

<b>Dimensions</b>			
<b>Length:</b>	5.3 in. (13.5 cm)		
<b>Height</b>	6.4 in. (16.3 cm)		
<b>Width:</b>	3.2 in. (8.1 cm)		
<b>Weight:</b>	7.5 oz. (213 g)		
<b>Housing:</b>	UL 94V0 grade		
<b>Power Requirements:</b>	4.5 - 12Vdc at scanner		
<b>Current Draw (Typical):</b>	<u>Input</u>	<u>Scanning</u>	<u>Idle</u>
	5 V	310mA	40mA
	12 V	130mA	35mA

## Power Supply

**Noise Rejection:** Maximum 100mV peak to peak, 10 to 100 kHz

## Environmental

<b>Temperature</b>	
<b>Operating:</b>	14°F to +122°F (-10°C to +50°C)
<b>Storage:</b>	-40°F to 140°F (-40°C to +60°C)
<b>Humidity:</b>	0 to 95%, non-condensing
<b>Sealing:</b>	IP54 (water and dust resistant)
<b>Mechanical Shock:</b>	Operational after 50 drops from 6.5 ft. (2 m) to concrete
<b>Ambient Light:</b>	Total darkness to 100,00 lux (full sunlight)
<b>ESD Protection:</b>	Functional after 100 discharges at 15kV
<b>Vibration:</b>	Withstands 5G peak from 22 to 300 Hz
<b>Agency:</b>	FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV
<b>MTBF:</b>	per MIL-HDBK-217F Ground Benign exceeds 82,000 hours

## Symbologies

<b>2 Dimensional:</b>	PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesas, Code 49, and UCC Composite.
<b>Linear:</b>	Codabar, Code 39 including PARAF, Interleaved 2 of 5, Code 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, RSS.
<b>Postal:</b>	Postnet, Planet Code, British Post, China Post, Canadian Post, Japanese Post, KIX (Netherlands Post)
<b>OCR Fonts:</b>	OCR-A, OCR-B
<b>Interfaces:</b>	All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, TTL level RS-232, TTL level Serial Wedge, USB, wand emulation, HHLC non-decoded laser compatible, True RS-232, IBM 468x, and IBM469x.
<b>Warranty:</b>	Three year factory warranty.



## Worldwide Offices

**Offices Serving North America**  
Skaneateles Falls, NY  
Tel: +1 315 685 8945  
or, in North America: +1 800 582 4263  
sales@hhp.com  
Charlotte, NC  
Tel: +1 704 998 3998  
or, in North America: +1 800 582 4263  
sales@hhp.com

**Offices Serving Europe, Middle East, and Africa**  
Europe  
Tel: +31 (0) 40 29 01 600  
euro\_sales@hhp.com  
United Kingdom  
Tel: +44 (0) 1 925 240055  
euro\_sales@hhp.com  
Italy  
Tel: +39 (0) 2 67 100752  
euro\_sales@hhp.com

**GOMARO s.a. - Switzerland**  
Tel: 021 869 97 70  
Fax: 021 869 96 02  
<http://www.gomaro.ch>

**Offices Serving Asia and the Pacific Rim**  
Hong Kong  
Tel: +852 2511 3050  
asia\_sales@hhp.com  
Japan  
Tel: +813 5842 6325  
asia\_sales@hhp.com

**Offices Serving Latin America**  
Naples, Florida  
Tel: +1 239 263 7600  
la-sales@hhp.com  
São Paulo  
Tel: +55 11 5016 3454  
la-sales@hhp.com  
Rio De Janeiro  
Tel: +55 21 2494 7060  
la-sales@hhp.com