

# PRODUCT SPECIFICATION

## STANDARD FEATURES

**Dimensions:** Height 13.75"(349 mm)  
Width 12.50"(317 mm)  
Depth 11.50"(292 mm)  
Weight 18 lbs.(8.1 kg)  
Shipping Weight 20 lbs.(9 kg)

**Monarch printers used with:** 1740™, 5170™, 9401™/9402™, 9403™, 9425™, 9445™, 9474™, 9840™, or 9850™

For 9401/9402, 9406 and 9446 printers, see instructions for adjustment to ensure print registration.

For 9840 and 9850 printers using 8.0 ips printing, you must use 3-inch or larger cores.

The maximum speed using the rewinder is 8.0 ips.

## PERFORMANCE

**Power:** U.S. - 115 VAC, 50/60 Hz  
International - 220/240 VAC  
50/60 Hz

## ENVIRONMENT RANGES

**Temperature:** Operating -  
40° to 110° F (4° to 43° C)  
Storage -  
15° to 120° F (-10° to 49° C)

**Relative Humidity:** Operating & Storage  
5% to 90% non-condensing

## SUPPLIES

**Supply roll sizes to use:** Inside diameter -  
1" (25 mm)  
3" (76 mm)  
4" (102 mm)  
Outside diameter -  
up to 12"(305 mm)

### Label dimensions to use:

**Widths -** 1" & 4" inside diameter cores:  
.75" to 3.37" using 3.62" hub length (19 mm to 86 mm using 92 mm)

.75" to 6.5" using 6.75" hub length (19 mm to 165 mm using 171 mm)

3" inside diameter cores:  
.75" to 2.5" using 3.62" hub length (19 mm to 64 using 92 mm)

.75" to 5.63" using 6.75" hub length (19 mm to 143 mm using 171.4 mm)

**Thickness -** .006" to .012"  
(.15 mm to .30 mm)


**Tag dimensions to use:** Widths - .75" to 6.5"  
(19 mm to 165 mm)

Thickness -.006" to .012"  
(.15 mm to .30 mm)

Rewinds tags or labels with or without cores.

# 415™ Rewind

REWINDS LABELS & TAGS



In our ongoing effort to deliver the best technology, specifications are subject to change without notice. A copy of the applicable written Monarch warranty statement is available upon request.

**Monarch®**  
**PAXAR**