

- Programmable Printer
- Integrated Printer with Optional Scanner
- Portable Printer
- Thermal Direct
- Custom Formatted
- Prints Receipts, Tags and Labels
- Supports TrueType® and Bitmapped Fonts



Monarch® Pathfinder® Ultra® Silver 6032™ Printer

STANDARD FEATURES

Dimensions:

Height – 6.5" (165 mm)
 Width – 7.75" (197 mm)
 Depth – 3.25" (83 mm)
 Weight – 1.973 lbs. (.90 kg)
 Shipping Wt. – 4.09 lbs. (1.86 kg)

Printing Method:

Thermal Direct

Printhead:

2.0" (50.8 mm)
 203 dots/inch (8 dots/mm)

Keypad/Display:

25 keys (inc. on/off) alpha/numeric supported
 2-line 15 character with backlight display feature

Memory:

1 MB RAM, 2 MB Flash

Bar Code Types:

UPCA +2/+5, UPCE +2/+5, EAN8 +2/+5, EAN13 +2/+5, Interleaved 2 of 5, Codabar, Code 128, Code 39, MSI

Standard Fonts:

Standard, Reduced, Bold, OCRA-like, EFF Swiss Bold*, HR1, and HR2 (HR1 and HR2 are only for numeric data.)

* Also available as a scalable font. The printer supports Bitmapped, TrueType® and International fonts.

Font Magnification:

1x to 7x for Bitmapped fonts
 4 to 250 pt. for scalable/TrueType fonts

Printer Warranty:

One (1) year parts and labor (ship-in). Full written warranty statement is available on request.

Printhead Warranty:

Six (6) months, or one million inches (1,000,000"), whichever occurs first.

Battery and Cable Warranty:

Three (3) Months pro-rated from date of shipment. Physical damage to the batteries or cables will not be covered by the limited warranty



Monarch® Pathfinder® Ultra® Silver 6032™ Printer

Page 2

SUPPLIES

Only Monarch® supplies are recommended. For high density and serial bar codes, Monarch "premium" supplies are recommended. The printer supports die cut, black mark, and non-indexed supplies.

Supply Types:

Tags, Labels, Linerless and Receipt Paper.

Supply Sizes:

Width – 1.2" to 2.0" (30 mm to 51 mm)
Length - .785" to 4.0" (20 mm to 102 mm)
Supply Roll lengths –
420" to 580" (10.7 to 14.7 meters)
Custom lengths are available, contact your Sales Representative for more details.

Supply Thickness:

Tags – 7 mils
Labels – 2.4 mils

Maximum Print Area:

1.89" x 3.837" (48 mm x 97 mm)

ENVIRONMENT RANGES

Operating Temperature:

40° to 104° F (4° to 40° C)

Storage:

15° to 120° F (-10° to 49° C)

Humidity/Operating and Storage:

5% to 90% non-condensing

Electrostatic Discharge and Air Quality:

Some problems with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. Paxar suggests that you take precautions to minimize these problems.

PERFORMANCE

Power Source:

7.4V Lithium Ion Battery Pack

Print Speed:

Up to 2 ips (51 mm)

Print Ratio:

30% black maximum per square inch

Inches per charge:

Up to 5,000" (127 meters) of 30% black printing on the supply. Factors such as scanning and duty cycle can reduce inches printed per charge.

Battery Cycle Life:

Approximately 300 full discharge cycles. Cycle life is approximate. Many factors effect an individual battery's performance.

Recommended Duty Cycle:

33% Duty Cycle (5 minutes out of 15 minutes time intervals). On-demand or intermittent printing has no restrictions.

OPTIONS

- Integrated Laser Scanner
-



ACCESSORIES

- On-Demand Sensor
- Battery (part#12009502)
- 9464™ Four Station Battery Charger
- 9462™ Single Station Battery Charger
- Hand Strap (part#124053)
- 6063™ AC Adapter
- 6076™ Cleaning Kit

In our ongoing effort to deliver the best technology, specifications are subject to change without notice.



PAXAR®

BC-SP-04 Rev. 10/04

e-mail: info@gomaro.ch
www.gomaro.ch

©2004 Paxar Americas, Inc.
All rights reserved.